

Wallop Bi-directional

2x8W



Housing Colors **BL** **WH**

Color Temperatures **3000K** **4000K**

Electrical Specification

Input AC Voltage (V)	ACC200-220V
Frequency (Hz)	50 Hz
Power Factor	>0.95
Current THD	<10%
Driver Efficiency	>85%
Inbuilt Surge Protection	3KV

Optical Parameters

Primary Optics	Lens: Tempered Glass Visor, Reflector: Tempered Glass Visor
Secondary Reflector	Silver Painted Polymer
Beam angle	80°
Beam Direction	Fixed

Product Material

Die Cast Aluminium

LED Parameters

CRI	>80
Binning	3 Step MacAdam
LED Lifetime	>50,000hrs
Lumen Output	2x598LM@3000K, 2x641LM@4000K
LED Chip	COB LED 36Vdc/350mA
LED Wattage	2x6.3W
System Wattage	2x7.2W

Ordering Code

Wallop Bidirectional - 2x8W -

Finish	CCT
<u>BL</u>	<u>3000K</u>

Modify ordering code from
given options:

WH	4000K
----	-------

Safety & General Features

Rohs - Lead Free Solder | Wires - Multi Core DC Output wire with connections Fire Retardant DC Wire |
Operating Ambient Temperature - 0° to 50°C | Ingress Protection - IP65

