

Wallop Unidirectional

8W | 15W



Housing Colors	BL	WH
Color Temperatures	3000K	4000K

Electrical Specification

Input AC Voltage (V)	ACC200-220V
Frequency (Hz)	50 Hz
Power Factor	>0.95
Current THD	<10%
Driver Efficiency	>85%
Inbuilt Surge Protection	3KV

Optical Parameters

Primary Optics	Lens: Tempered Glass Visor, Reflector: Tempered Glass Visor
Secondary Reflector	Silver Painted Polymer
Beam angle	80°
Beam Direction	Fixed

Product Material

Die Cast Aluminium

LED Parameters

CRI	>80
Binning	3 Step MacAdam
LED Lifetime	>50,000hrs

Wattage	Output@3000K	Output@4000K	LED used	LED power/System power
8W	598lm	641lm	COB LED 36Vdc/190mA	6.3/7.2W
15W	2926lm	3086lm	Mid Power LED Array 33-36Vdc/700mA	23.1/26.6W

Ordering Code

	Power	Finish	CCT
Wallop Unidirectional	8W	BL	3000K

Modify ordering code from
given options:

15W	WH	4000K
-----	----	-------

Safety & General Features

Rohs - Lead Free Solder | Wires - Multi Core DC Output wire with connections Fire Retardant DC Wire |
Operating Ambient Temperature - 0° to 50°C | Ingress Protection - IP65

