

Mik mini | 1W



Housing Colors

BL

WH

Color Temperatures

3000K

4000K

Electrical Specification

Input AC Voltage (V)	ACC200-220V
Frequency (Hz)	50 Hz
Driver operating Voltage	350mA 2-3V DC
Power Factor	>0.95
Current THD	<10%
Driver Efficiency	>85%
Inbuilt Surge Protection	3KV

Optical Parameters

Primary Reflector	PMMA Lens
Secondary Reflector	-
Beam Angle	25°/40°/75°/92°
UGR	<20
Beam Direction	Fixed

Product Material


Die Cast Aluminium, Milled Aluminium

LED Parameters

CRI	>90
Binning	3 Step MacAdam
LED Lifetime	>50000hrs
Lumen output (for 27)	114LM@3000K, 119LM@4000K
LED Chip	SMD 2-3Vdc/350mA
LED Wattage	1.4W
System Wattage	1.7W

Ordering Code

	Body Finish	CCT	Beam Angle
Mik mini - 1W -	BL	3000K	25°
Modify ordering code from given options:	WH	4000K	40°/75°/92°



Platforms/Protocols supported



Safety & General Features

Rohs - Lead Free Solder | Wires - Multi Core DC Output wire with connections Fire Retardant DC Wire | Operating Ambient Temperature - 10° to 50°C
Ingress Protection - IP20 | Mounting Parameters - Recess Mounting for Ceiling with Toggle option.