


Cylux P OPD | 12W



Housing Colors



Color Temperatures



Electrical Specification

Input AC Voltage (V)	ACC200-220V
Frequency (Hz)	50 Hz
Driver operating Voltage	300mA 36V DC
Power Factor	>0.95
Current THD	<10%
Driver Efficiency	>85%
Inbuilt Surge Protection	3KV

Optical Parameters

Primary Reflector	Reflector - White optics
Diffuser	Opal PC
Beam Angle	88°
UGR	<28
Beam Direction	Fixed

Product Material


Die Cast Aluminium, Milled Aluminium

LED Parameters

CRI	>90
Binning	3 Step MacAdam
LED Lifetime	>50000hrs
Lumen output (for 27)	1145LM@3000K, 1204LM@4000K
LED Chip	Mid power LED array 32V-36Vdc/300mA
LED Wattage	10.3W
System Wattage	11.8W

Ordering Code

	Body Finish	CCT	Beam Angle
Cylux P OPD - 12W	- <u>BL</u>	- <u>3000K</u>	- <u>88°</u>
<small>Modify ordering code from given options:</small>	WH	4000K/TW	



Platforms supported



Safety & General Features

Rohs - Lead Free Solder | Wires - Multi Core DC Output wire with connections Fire Retardant DC Wire | Operating Ambient Temperature - 10° to 50°C
Ingress Protection - IP20 | Mounting Parameters - Pendant Mounting for Ceiling with Length option.