

Bloom Dark 48V | 9W



Housing Colors

BL

WH

Color Temperatures

3000K

4000K

Electrical Specification

Input AC Voltage (V)	48V
Frequency (Hz)	50 Hz
Driver operating Voltage	250mA 36V DC
Power Factor	>0.95
Current THD	<10%
Driver Efficiency	>85%
Inbuilt Surge Protection	3KV

Optical Parameters


Primary Optics	PMMA Lens, PC Metallised Reflector
Secondary Optics	Anodised Reflector
Beam Angle	46°
UGR	<19
Beam Direction	Fixed

Product Material

Pressure Die Cast Heat Sink & Aluminum Front Ring

LED Parameters

CRI	>90
Binning	3 Step MacAdam
LED Lifetime	>50000hrs
Lumen output	731LM@3000K, 773LM@4000K
LED Chip	High Power LED 33-36Vdc/250mA
LED Wattage	9W



Platforms/Protocols supported



Ordering Code

	Body Finish	CCT
Bloom Dark 48V - 9W	BL	3000K
	WH	4000K

Modify ordering code from given options:

Safety & General Features

Rohs - Lead Free Solder | **Wires** - Multi Core DC Output wire with connections Fire Retardant DC Wire | **Operating Ambient Temperature** - 10° to 50°C
Ingress Protection - IP20 | **Mounting Parameters** - Track mounting for ceiling with toggle option for quick, safe, and easy installation.