

Cylux P MPD | 10W



Housing Colors

BL **WH**

Color Temperatures

3000K **4000K** **TW**

Electrical Specification

Input AC Voltage (V)	ACC200-220V
Frequency (Hz)	50 Hz
Driver operating Voltage	250mA 36V DC
Power Factor	>0.95
Current THD	<10%
Driver Efficiency	>85%
Inbuilt Surge Protection	3KV

Optical Parameters

Primary Reflector	Reflector - White optics
Diffuser	Micropismatic
Beam Angle	74°
UGR	<23
Beam Direction	Fixed

Product Material


Die Cast Aluminium, Milled Aluminium

LED Parameters

CRI	>90
Binning	3 Step MacAdam
LED Lifetime	>50000hrs
Lumen output (for 27)	747LM@3000K, 788LM@4000K
LED Chip	Mid power LED array 32V-36Vdc/250mA
LED Wattage	8.8W
System Wattage	10.1W

Ordering Code

	Body Finish	CCT	Beam Angle
Cylux P MPD - 10W	<u>BL</u>	<u>3000K</u>	<u>74°</u>
Modify ordering code from given options:	WH	4000K/TW	



Platforms/Protocols supported



Safety & General Features

Rohs - Lead Free Solder | **Wires** - Multi Core DC Output wire with connections Fire Retardant DC Wire | **Operating Ambient Temperature** - 10° to 50°C
Ingress Protection - IP20 | **Mounting Parameters** - Pendant Mounting for Ceiling with Lenght option.